

# MAGNUM (MG) – kategorie D

Váha (g/m <sup>2</sup> ) – Weight (g/m <sup>2</sup> )	EN 12127	± 5 %	715
Výška (cm) – Width (cm)	-----	± 2 %	140
Otěruvzdornost (cykly) Abrasion resistance (rubs)	ISO 5470-2 (Martindale)		200.000
Barevná stálost na světle (modrá stupnice) Light fastness (blue scale)	ISO 105-B02 (Xenotest)		7
Stálost barvy při otěru (stupnice šedé) Fastness to rubbing (grey scale)	ISO 105-X12 (Crockmeter)		5
Složení – Composition	1% polyurethane/polycarbonate, 31% Bio-based pvc, 49% Standard pvc, 19% Tencel		
Všechny certifikáty – Certificates available			
<p>1IM - UNI 9175; EN 1021 1/2;            BS 5852 part 1, is 0 and 1; BS 5852 crib 5;            BS 7176 + A1 medium hazard; NF D60-013 (AM.18);            NFPA 260 Class 1; California TB 117-2013;            IMO 3.20 - FTP Code 307 part 8;            ÖNOM B 3825 - schwer brennbar            available at <a href="http://antares.cz">antares.cz</a></p>			
Čištění a údržba potahů – Cleaning and washing			
<p>Maintenance in healthcare - routine maintenance do not expose the material to direct sunlight. Late removal of dirt reduces cleaning success. The shade and pattern of the fabric may differ slightly from the swatch for technological reasons. MAGNUM MATERIAL SHEET tested maintenance with chlorine-based disinfectants (Medicarine 1‰ solutions, HAZ 5‰ to 1%, Tristel disinfectant spray, cleaning wipes containing isopropanol 70%). A minor change in color and hardness of the material may occur. Dirt can be wiped off with a soft cloth soaked in a neutral soapy solution. Absorb liquid dirt with a paper towel. Do not use chemical solvents.</p>			

# MAGNUM (MG) – kategorie D

Dostupné v 62 barvách / Available in 62 colors



# MAGNUM (MG) – kategorie D

---

