

RELIFE (RF)

Váha (g/m²) - <i>Weight (g/m²)</i>	EN 12127	± 5 %	460
Výška (cm) - <i>Width (cm)</i>	-----	± 2 %	140
Otěruvzdornost (cykly) <i>Abrasion resistance (rubs)</i>	ISO 12947-2 (Martindale)	± 10 %	100.000
Barevná stálost na světle (modrá stupnice) <i>Light fastness (blue scale)</i>	ISO 105-B02 (Xenotest)	1 - 8	4/5
Stálost barvy při otěru (stupnice šedé) <i>Fastness to rubbing (grey scale)</i>	ISO 105-X12 (Crockmeter)	4 - 5	4/5
Pilling (2000 cyklů) - <i>Pilling (2000 rubs)</i>	ISO 12945-2	4 - 5	4/5
Složení - <i>Composition</i>	100% Post-consumer Recycled Polyester		
Všechny certifikáty - <i>All certificates available</i>			
EN 1021 1/2 BS 5852 0 BS 7176 Low Hazard CAL TB 117 Section 1 NFPA 260 Class 1 IMO MSC.307 (88) Annex I Part 8 <i>available at antares.cz</i>			
Čištění a údržba potahů – <i>Cleaning and washing</i>			
<i>Vacuum regularly. In case of stains, use a damp cloth with neutral soap suitable for cleaning of upholstery products.</i>			

RELIFE (RF)

Dostupné v 15 barvách *Available in 15 colours*




RF001

RF002

RF003

RF004

RF005



RF006

RF008

RF009

RF010

RF011



RF012

RF013

RF014

RF015

RF018

